

**PAT-NO:** JP403025737A  
**DOCUMENT-IDENTIFIER:** JP 03025737 A  
**TITLE:** MAGNETO-OPTICAL RECORDING MEDIUM  
**PUBN-DATE:** February 4, 1991

**INVENTOR-INFORMATION:**

NAME	COUNTRY
TOMIE, TAKASHI	
KINOSHITA, KIMIO	
SUZUKI, KAZUTOMI	
NAKATANI, TADANORI	
CHIBA, KIYOSHI	

**ASSIGNEE-INFORMATION:**

NAME	COUNTRY
TEIJIN LTD	N/A

**APPL-NO:** JP01162018  
**APPL-DATE:** June 23, 1989

**INT-CL (IPC):** G11B011/10

**US-CL-CURRENT:** 369/283

**ABSTRACT:**

**PURPOSE:** To obtain the magneto-optical recording medium having a high sensitivity and high C/N by forming a metal reflecting layer of an Ag alloy which is formed by incorporating 0.5 to 30at.% Au into Ag and further incorporating 0.5 to 15at.% at least one kind of Ta or Ti therein.

**CONSTITUTION:** The AgCu alloy film is formed by a high-frequency sputtering method on a substrate consisting of glass, acrylic resin, etc. The AgCu alloy film is formed by adding 0.5 to 30at.% Cu to the Ag, by which the high reflectivity is obtd. The reflectivity is not lowered even if the film is rested over a long period of time. In addition, the film has durability as well. The reflectivity degrades in a short period of time if the content of the Cu is smaller than 0.5at.% or larger than 30at.%. The recording sensitivity and the durability are greatly improved if at least one kind of the Ta or Ti is added at 0.5 to 15at.% to the AgCu film. There is no effect of improving the sensitivity if the content of the Ta and Ti is smaller than this range. The reflectivity is low and the C/N is poor as well if the content exceeds this range.

**COPYRIGHT:** (C)1991,JPO&Japio